

High Temperature Spray Coating Adhesive PET Green Tape



GREEN TAPE FILM FOR GLASS PAINTING GLAZING  
GREEN THERMAL TAPE FILM  
HEAT RESISTANCE GREEN TAPE FILM  
HIGH TEMPERATURE GREEN TAPE FILM

980mm\*66M/roll

25mm\*66M/roll

30mm\*66M/roll

40mm\*66M/roll

50mm\*66M/roll

UCOLIN



1)-Excellent tensile strength and welding strength: The GREEN PET TAPE FILM has been used for many heavy packages.

2)-Excellent tension maintenance. The GREEN PET TAPE FILM can maintain tensile strength for long time stretch with minimized strap slacking, at the same time ensuring excellent shock resistance, making GREEN PET TAPE FILM ideal for long-distance, long-period transportation.

3)-Excellent rusty and chemical resistance: Allowing direct strapping with The GREEN PET TAPE FILM without products damage or rusty.

4)-Ultra weather resistance: The GREEN PET TAPE FILM stays stabile under temperature of -50° C ~100° C, which ensures GREEN PET TAPE FILM is widely applied under any conditions.

980mm\*66M/roll

600mm\*66M/roll

25mm\*66M/roll

30mm\*66M/roll

40mm\*66M/roll

50mm\*66M/roll

TESTED ITEM	GREEN TAPE
Color	Green
Sealant Materials	Silicone
Sealant Materials Thickness	$0.035 \pm 0.005\text{mm}$
Thickness of Tape Sheet	$0.06 \pm 0.005\text{mm}$
Temperature Resistance	180℃ Continuously heating 200℃ Discontinuously heating
Tear Strength	120 N/25mm
Adhesive Strength	7.5 N/25mm
Elongation	55%
Volage Resistance	5 KV
Insulation Resistance	1,000,000 MΩ
Insulation Grade	F

UCOLIN

**GREEN TAPE  
GREEN THERMAL TAPE  
GREEN RIBBON TAPE  
HIGH TEMPERATURE GREEN TAPE**

**25mm\*66M/roll**

**30mm\*66M/roll**

**40mm\*66M/roll**

**50mm\*66M/roll**

**UC@UCOLIN.COM**

Zac Lynn  
uc@ucolin.com

UCOLIN

UCOLIN

1260°C Ceramic Fiber Paper  
for Fusion Kiln  
for EVA Glass Laminating Furnace Oven  
[UC@UCOLIN.COM](mailto:UC@UCOLIN.COM)

UCOLIN

[www.UCOLIN.com](http://www.UCOLIN.com)  
[UC@UCOLIN.COM](mailto:UC@UCOLIN.COM)  
GD, CHINA